



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226	C-tol. %	Dimensions b x h x l	P mm	It mm
450	2.2	DAL225KM02	± 10	11.0 x 21.0 x 31.0	27.5 \pm 0.4	3.5 \pm 0.3

Same as P226DAL225KAGJ or P226DAL225KM01

<But>

- Automotive(AEC-Q200 Qualified)
- 3011 PBT gray case & LT3.5 \pm 0.3mm
- Marking

2u2 K 450V PILKOR
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray arrange)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40239	8242 456 20016	100ea (8242 451 31051)	800ea (8242 451 30941)

- Test Requirements

See P226xxxxxxxM...(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	18-01-25
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (두원전자)	P226DAL225KM02			개정 No	
승인	강 문 현					190-1	of page

For part lists see P226DAL225KAGJ

Include :

Delete :

- Cell code : 4342 504 S0027 (P226DAL225KM01 & P226DAL225KM02)

For manufacturing instruction see P226DAL225KAGJ

But,

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 3011 PBT (gray) case : 4342 433 20211

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-01-25
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (두원전자)	P226DAL225KM02		개정 No	
승인	강 문 현		260-1	of page	1	개정일자