



$d_t = 1.0 \pm 0.1 \text{ mm}$

Voltage Vdc	Cap. $\mu\text{F}$	Code P226 .....	C-tol. %	Dimensions b x h x l	P mm	It mm
450	5.6	DAL565KM01	$\pm 10$	18.0 x 28.0 x 31.0	27.5 $\pm$ 0.7	5.0 $\pm$ 1.0

Same as P226DAL565KAGJ

<But>

- Automotive (AEC-Q200 Qualified)
- PBT Gray & Cu 1.0 $\Phi$
- Marking

5u6 K 450V PILKOR  
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray arrange)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40241	8242 456 20016	60ea (8242 451 31051)	360ea (8242 451 30941)

- Test Requirements

See P226xxxxxxxM....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-08-17
작성	김 세 지	MKP RADIAL POTTED CAPACITORS (LG전자)	P226DAL565KM01			개정 No	1
승인	강 문 현					190-1	of page

---

For part lists see P226DAL565KAGJ

---

Include :

Delete :

- Cell code : 4342 504 S0015

---

For manufacturing instruction see P226DAL565KAGJ

---

But,

- LOA

1) Pull off force  $\geq$  1000g

2) 3018PBT gray : 4342 433 20261

3) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

4) Wire Cu 1.0 $\Phi$

박 현 숙		MKP RADIAL POTTED CAPACITORS ( LG전자 )	P226DAL565KM01		16-08-17			
백 영 섭					QS	A4		
			16-08-17	1	260-1	010	QS	A4
QS	강문현	PILKOR ELECTRONICS 2016						