



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226	C-tol. %	Dimensions b x h x l	P mm	It mm
600	1.0	FAL105KM01	±10	11.0 x 21.0 x 31.0	27.5±0.4	3.7±0.3

Same as P226FAL105KAGJ

<But>

- Automotive(AEC-Q200 Qualified)
- Rated voltage 600Vdc
- Marking

1u K 600V PILKOR
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray arrange)

Packing method	SPQ (Tray)	SPQ (Bundle)	PQ (Outer box)
8242 450 40262	100ea (8242 451 31051)	400ea	800ea (8242 451 30941)

- Test Requirements

See P226xxxxxxxM....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-07-01
작성	백영섭	MKP RADIAL POTTED CAPACITORS (LG전자)	P226FAL105KM01		개정 No	4	
승인	강문현		190-1	of page	1	개정일자	17-07-10

For part lists see P226FAL105KAGJ

Include :

Delete :

- Cell code : 4342 504 S0007

For manufacturing instruction see P226FAL105KAGJ

But,

- LOA

1) Welding depth ; 0.5 ± 0.1 mm

2) Pull off force ≥ 1000 g

3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

박 현 숙		MKP RADIAL POTTED CAPACITORS (LG전자)				P226FAL105KM01		16-07-01	
백 영 섭								QS	A4
			16-07-01	1	260-1	010			
QS	강문현		PILKOR ELECTRONICS 2016						