



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226	C-tol. %	Dimensions b x h x l	P mm	lt mm
630	2.2	J63225KM01	±10	13.0 x 23.0 x 26.0	22.5±0.4	5.0±1.0

Same as P226L63225KASL

<But>

- 2513PBT gray case
- Dissipation factor (Tan δ, x 10⁻⁴); ≤ 10 at 1kHz
- Insulation resistance ; RC > 15, 000 s (at 500V for 1min.)
- Rated voltage pulse lode slope(dV/dt)_R : 110V/us
- Marking

2u2 K 630V PILKOR
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Loose in box)

Packing method	SPQ (Inner box)	PQ (Outer box)
8242 450 40027	500ea (8242 451 30221)	2000ea (8242 451 30311)

부서	제품개발1팀	Type Specification			최초작성일	18-05-25
작성	백영섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P226J63225KM01		개정 No	
승인	강문현		190-1	of page	1	개정일자

For part lists see P226L63225KASL

Include :

Delete :

- Cell code : 4342 504 S0034

For manufacturing instruction see P226L63225KASL

But,

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

2) PBT case (Gray) ; 4342 433 20181

- R/D Testing

Tan d		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	180	-9.5%/+ 9.0%	500	36	1010V

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-05-25
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P226J63225KM01			개정 No	
승인	강 문 현		260-1	of page	1	개정일자	