



$$d_t = 1.0 \pm 0.1 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226	C-tol. %	Dimensions b x h x l	P mm	lt mm
250	10	L25106KM01	± 10	21.0 x 31.0 x 31.0	27.5 \pm 0.7	5.0 \pm 1.0

Same as P226L25106KAS2

<But>

- Automotive(AEC-Q200 qualified)
- 3021 PBT gray case & lead wire 1.0 Φ
- Marking

10u K 250V PILKOR
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray packing)

Packing method	Sponge	SPQ (Inner box)	PQ (Outer box)
8242 450 40241	8242 456 20016	50ea (8242 451 31051)	300ea (8242 451 30941)

- Test Requirements

See P226xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	19-10-10
작성	백영섭	MKP RADIAL POTTED CAPACITORS (대우전자부품)	P226L25106KM01		개정 No		
승인	강문현				190-1	of page	1

For part lists see P226L25106KAS2

Include :

Delete :

- Cell code for P226L25106KM01 : 4342 504 S0056

For manufacturing instruction see P226L25106KAS2

But,

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 3021PBT_Gray : 4342 433 20281
- 3) Lead wire 1.0Φ

- R/D Testing

Tan d (x 10 ⁻⁴)			Cap test limit	R. insul		Healing & Test Voltage
1kHz	10kHz	100kHz		V	nA	
10	30	500	-9.5%/+ 9.0%	100	66	400V

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-10-10
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (대우전자부품)	P226L25106KM01			개정 No	
승인	강 문 현		260-1	of page	1	개정일자	