



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226 .....	C-tol. %	Dimensions b x h x l	P mm	lt mm
250	4.7	L25475KM01	±10	13.0 x 23.0 x 31.0	27.5±0.4	5.0±1.0

Same as P226L25475KAS2

<But>

- Automotive(AEC-Q200 qualified)

- Marking

4u7 K 250V PILKOR  
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray packing)

Packing method	Sponge	SPQ ( Tray )	PQ ( Outer box )
8242 450 40241	8242 456 20016	85ea ( 8242 451 31051 )	510ea ( 8242 451 30941 )

- Test Requirements

See P226xxxxxxxM....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	19-10-07
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (경신)	P226L25475KM01		개정 No		
승인	강 문 현		190-1	of page	1	개정일자	

For part lists see P226L25475KAS2

Include :

Delete :

- Cell code : 4342 504 S0055

For manufacturing instruction see P226L25475KAS2

But,

- LOA

- 1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )
- 2) 3013PBT\_Gray : 4342 433 20221

- R/D Testing

Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
9	250	-9.5%/+ 9.0%	100	31	400V

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-10-07
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (경신)	P226L25475KM01			개정 No	
승인	강 문 현		260-1	of page	1	개정일자	