



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code P226	C-tol. %	Dimensions b x h x l	P mm	lt mm
630	1.5	L63155KM01	±10	13.0 x 23.0 x 31.0	27.5±0.4	5.0±1.0

Same as P226L63155KAS2

<But>

- Automotive(AEC-Q200 qualified)
- Value extension : 1.5uF / 3013 PBT gray case
- Marking

1u5 K 630V PILKOR
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray packing)

Packing method	Sponge	SPQ (Inner box)	PQ (Outer box)
8242 450 40241	8242 456 20016	85ea (8242 451 31051)	510ea (8242 451 30941)

- Test Requirements

See P226xxxxxxxM....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-08-28
작성	백영섭	MKP RADIAL POTTED CAPACITORS (경신)	P226L63155KM01		개정 No	
승인	강문현		190-1	of page 1	개정일자	

For part lists see P226L63155KAS2

Include :

Delete :

- Cell code : 4342 504 S0041

For manufacturing instruction see P226L63155KAS2

But,

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 3013PBT_Gray : 4342 433 20221

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
9	160	-9.5%/+ 9.0%	500	50	1010V

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-08-28
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (경신)	P226L63155KM01			개정 No	
승인	강 문 현		260-1	of page	1	개정일자	