



$$d_t = 1.0 \pm 0.1 \text{ mm}$$

Voltage Vdc	Cap. $\mu\text{F}$	Code P226 .....	C-tol. %	Dimensions b x h x l	P mm	lt mm
630	3.9	L63395KM01	$\pm 10$	21.0 x 31.0 x 31.0	27.5 $\pm$ 0.7	3.5 $\pm$ 0.5

Same as P226L63395KA52

<But>

- Automotive(AEC-Q200 qualified)
- Lead wire 1.0 $\Phi$  & Lt 3.5 $\pm$ 0.5mm
- Marking

3u9 K 630V PILKOR  
PCPW 226 MKP WK....

Marking on the top or side

- Packing Method (Tray packing)

Packing method	Sponge	SPQ	PQ
		( Inner box )	( Outer box )
8242 450 40253	8242 456 20016	50ea ( 8242 451 31051 )	500ea ( 8242 451 31061 )

- Test Requirements

See P226xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	19-05-10
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (영화테크)	P226L63395KM01		개정 No		
승인	강 문 현				190-1	of page	1

For part lists see P226L63395KA52

Include :

Delete :

- Cell code for P226L63395KM01 : 4342 504 S0052

For manufacturing instruction see P226L63395KA52

But,

- LOA

1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

2) 3021PBT\_Gray : 4342 433 20281

- R/D Testing

Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
9	200	-9.5%/+ 9.0%	500	130	1010V

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-05-10
작성	백영섭	MKP RADIAL POTTED CAPACITORS (영화테크)	P226L63395KM01			개정 No	
승인	강문현		260-1	of page	1	개정일자	