



$dt = 0.8+0.08/-0.05\text{mm}$

Voltage Vdc	Cap. μF	Code P246	C-tol. %	Dimensions b x h x l mm	P mm	lt mm
1000	1.5	L10155JM01	± 5	13.0 x 23.0 x 31.0	27.5 \pm 0.4	3.5 \pm 0.3

Same as P246L11155JA52

<But>

- Automotive(AEC-Q200 Qualified)
- Rated voltage 1000Vdc
- Marking

1u5 J 1000V PILKOR
PCPW 246 MKP WK....

Marking on the top

- PACKING METHOD (Tray arrange)

Packing method	Sponge	Tray	PQ
		(Inner box)	(Outer plastic box)
8242 450 40252	8242 456 20016	85 (8242 451 31051)	1020 (8242 451 31061)

-Test Requirements

See P246xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	18-06-27
작성	백영섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P246L10155JM01		개정 No		
승인	강문현		190-1	of page	1	개정일자	

For part lists see P246L11155JA52

Include :

Delete :

- Cell code :

. 4342 507 S0009

For manufacturing instruction see P246L11155JA52

-. 3013PBT Gray case : 4342 433 20221

-. Epoxy : 770D

<But>

- RD

Voltage (V)	Cap (uF)	Tan δ ($\times 10^{-4}$)		Cap. limit	R.insul		Test voltage
		1kHz	10kHz	%	V	nA	V
1000	1.5	10	40	+4.5/-4.5	500	150	1600

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-06-27
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)		P246L10155JM01		개정 No	
승인	강 문 현					260-1	of page