



$$d_t = 1.0 \pm 0.1 \text{ mm}$$

Voltage Vdc	Cap. $\mu\text{F}$	Code P246 .....	C-tol. %	Dimensions b x h x l mm	P mm	lt mm
1100	3.0	L11305KM01	$\pm 10$	18.0 x 28.0 x 31.0	27.5 $\pm$ 0.7	3.5 $\pm$ 0.3

Same as P246L11305JA52

<But>

- Automotive(AEC-Q200 Qualified)
- Cap. Tolerance  $\pm 10\%$  & Lead Wire 1.0 $\Phi$
- Marking

3u K 1100V PILKOR  
PCPW 246 MKP WK....

Marking on the top

- PACKING METHOD (Tray)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40253	8242 456 20016	60 (8242 451 31051)	600 (8242 451 31061)

-Test Requirements

See P246xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	18-05-14
작성	백영섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P246L11305KM01		개정 No		
승인	강문현		190-1	of page	1	개정일자	

---

For part lists see P246L11305JA52

---

Include :

Delete :

- Cell code :

. 4342 507 S0005

---

For manufacturing instruction see P246L11305JA52

---

<But>

- LOA

: Lead wire 1.0Φ

- RD

Voltage (V)	Cap (uF)	Tan δ ( x 10 <sup>-4</sup> )		Cap. limit %	R.insul		Test voltage V
		1kHz	10kHz		V	nA	
1100	3.0	10	40	+9.0/-9.0	500	300	1760

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-05-14
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)		P246L11305KM01		개정 No	
승인	강 문 현					260-1	of page