



dt = 1.0±0.1mm

Voltage Vdc	Cap. μF	Code P246	C-tol. %	Dimensions b × h × l mm	P mm	It mm
900	6.0	L90605JM01	±5	21.0 x 31.0 x 31.0	27.5±0.7	3.5±0.5

Same as P246L90605JA52

<But>

- . Automotive(AEC-Q200 Qualified)
- . Lead wire 1.0Φ
- . Marking

6u J 900V PILKOR PCPW 246 MKP WK...
--

Marking on the top or side

- . PACKING METHOD (Tray arrange)

Packing method	Sponge	Tray	PQ
		(Inner box)	(Outer plastic box)
8242 450 40253	8242 456 20016	50 (8242 451 31051)	500 (8242 451 31061)

- . Test Requirements

See P246xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	19-03-25
작성	백영섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P246L90605JM01		개정 No		
승인	강문현		190-1	of page	1	개정일자	

For part lists see P246L90605JA52

Include :

Delete :

- Cell code :

. 4342 507 S0022

For manufacturing instruction see P246L90605JA52

<But>

-. LOA

: Lead wire 1.0Φ (0142 400 00025)

-. R/D

Voltage (V)	Cap (uF)	Tan δ (x 10 ⁻⁴)		Cap. limit	R.insul		Test voltage
		1kHz	10kHz	%	V	nA	V
900	6	10	50	+4.5/-4.5	500	600	1440

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-03-25
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)		P246L90605JM01		개정 No	
승인	강 문 현					260-1	of page