



$$d_t = 1.2 \pm 0.12\text{mm}$$

Voltage Vdc	Cap. $\mu\text{F}$	Code P246 .....	C-tol. %	Dimensions b x h x l mm	P mm	P1 mm	lt mm
900	35	T90356JM01	$\pm 5$	35.0 x 50.0 x 57.0	52.5 $\pm$ 0.7	20.3 $\pm$ 0.5	3.5 $\pm$ 0.5

Same as P246T90356JA54

<But>

- Automotive(AEC-Q200 Qualified)
- Marking

35u J 900V PILKOR  
PCPW 246 MKP WK....

Marking on the top

- PACKING METHOD (Arrange)

Packing method	Sponge	SPQ (Folding Plate )	PQ ( Outer box )
8242 450 40265	8242 456 20018	35 ( 8242 451 10301 )	105 ( 8242 451 31091 )

- Test Requirements

See P246xxxxxxxMxx (sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	19-03-06
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)	P246T90356JM01		개정 No	
승인	강 문 현				190-1	of page

For part lists see P246T90356JA54

Include :

Delete :

- Cell code : 4342 507 S0019

For manufacturing instruction see P246T90356JA54

<공통>

- LOA

1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

2) 5735 PBT Gray case : 4342 433 20471

- RD

Voltage (V)	Cap (uF)	Tan δ ( x 10 <sup>-4</sup> )		Cap. limit	R.insul		Test voltage
		1kHz	10kHz	%	V	nA	V
900	35	20	140	+4.5/-4.5	500	3500	1440

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-03-06
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (현대모비스)		P246T90356JM01		개정 No	
승인	강 문 현					260-1	of page