



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V ^r	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
1600V	0.01	SA002	±5.0 %	8.5 x 15.0 x 18.0	15.0±0.4	5.0±1.0

Same as PCMP 384 82103

<But>

- Automotive (AEC-Q200 Qualified)

- Packing Method (LOOSE IN BOX)

12 NC	Packing method	SPQ	PQ
PCMP 384 SA002	8242 450 40025	1000 (8242 451 30201)	4000 (8242 451 30291)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	15-04-01
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (LS산전)	PCMP 384 SA002		개정 No	1	
승인	강 문 현		190-1	of page	1	개정일자	16-11-23

For part lists see PCMP 384 82103

Include :

- Cell code :

. 4342 472 S0183

Delete :

For manufacturing instruction see PCMP 384 82103 However :

<But>

- LOA

1) Welding depth ; 0.5 ± 0.1 mm

2) Pull off force ≥ 1000 g

3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

박 주 영		MMKP RADIAL POTTED CAPACITORS (LS산전)	PCMP 384 SA002		15-04-01			
백 영 섭								
			15-04-01	1	260-1	010	QS	A4
QS	박 범 학	(C) PILKOR ELECTRONICS CO., LTD. 2015						