



$$d_t = 0.6 + 0.06/-0.05 \text{ mm}$$

Voltage V [⊖]	Cap. μF	Code PCMP 384	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
630	0.0062	SA011	±5 %	4.0 x 10.0 x 12.5	10.0±0.4	3.4±0.3
250	0.022	SA012	±5 %	4.0 x 10.0 x 12.5	10.0±0.4	3.4±0.3

Same as PCMP 384 C2622 / 42223

<But>

- Automotive (AEC-Q200 Qualified)
- 1240 PBT gray case
- LT=3.4±0.3mm

- Packing Method (Vinyl Packing)

Packing method	Vinyl	SPQ	PQ
8242 450 40094	500 (8242 456 40003)	2000 (8242 451 30181)	8000 (8242 451 30271)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	15-12-11
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (LGIT)	PCMP 384 SA011 PCMP 384 SA012		개정 No	1
승인	강 문 현		190-1	of page 1	개정일자	16-11-23

For part lists see PCMP 384 C2622 / 42223

Include :

Delete :

- Cell code :

. 4342 472 S0193(for PCMP 384 SA011)

. 4342 472 S0194(for PCMP 384 SA012)

For manufacturing instruction see PCMP 384 C2622 / 42223 However :

<But>

- LOA

1) Welding depth ; 0.5 ± 0.1 mm

2) Pull off force ≥ 1000 gf

3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

4) 1240 PBT gray case – 4342 433 20001

박 주 영		MMKP RADIAL POTTED CAPACITORS (LGIT)			PCMP 384 SA011	15-12-11	
백 영 섭					PCMP 384 SA012		
			15-12-11	1	260-1	010	QS A4
QS	강 문 현	PILKOR ELECTRONICS 2015					