



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V [±]	Cap. μF	Code PCMP 384	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
630	0.30	SA022	±5 %	11.0 x 21.0 x 31.0	27.5±0.4	3.4±0.3

Same as PCMP 384L12304

<But>

- Automotive (AEC-Q200 Qualified)
- 3011 PBT gray case & LT 3.4±0.3mm
- Marking

300n J 630V **PILKOR**
384 MMKP WK....

Marking on the side or top

- Packing Method (Tray arrange)

Packing method	Sponge	SPQ(tray)	PQ
8242 450 40239	8242 456 20016	100 (8242 451 31051)	800 (8242 451 30941)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-10-21
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA022		개정 No	1	
승인	강 문 현		190-1	of page	1	개정일자	16-11-23

For part lists see PCMP 384L12304

Include :

Delete :

- Cell code : 4342 472 S0207 for PCMP 384 SA022

For manufacturing instruction see PCMP 384L12304 However :

<But>

- LOA

- 1) Pull off force $\geq 1000\text{gf}$
- 2) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 3) 3011 PBT gray case – 4342 433 20211

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
7	30	-4.5%/+ 4.5%	500	5	1050V

박 현 속		MMKP			PCMP 384 SA022		16-10-21	
백 영 섭		RADIAL POTTED CAPACITORS						
		(LG전자)						
			16-10-21	1	260-1	010	QS	A4
QS	강 문 현	PILKOR ELECTRONICS 2016						