



$$d_t = 0.6 + 0.06/-0.05 \text{ mm}$$

Voltage V [∘]	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
630	0.0022	SA032	±5 %	5.0 × 11.0 × 12.5	10.0±0.4	3.5±0.3

Same as PCMP 384 12222 or SA021

<But>

- Automotive (AEC-Q200 Qualified)
- 1250 PBT gray case & LT3.5±0.3mm
- Marking

2n2 J 630V
384 MMKP
PILKOR

Marking on the side

- Packing Method (Vinyl)

Packing method	Vinyl	SPQ	PQ
8242 450 40122	250 (8242 456 40006)	1500 (8242 451 30191)	6000 (8242 451 30281)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-01-25
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (두원전자)	PCMP 384 SA032		개정 No	
승인	강문현		190-1	of page	1	개정일자

For part lists see PCMP 384 12222

Include :

Delete :

- Cell code : 4342 472 S0206 for PCMP 384 SA021 or PCMP 384 SA032

For manufacturing instruction see PCMP 384 12222 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

2) 1250 PBT gray case – 4342 433 20011

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
7	10	-4.5%/+ 4.5%	500	5	1010V

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-01-25
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (두원전자)	PCMP 384 SA032		개정 No		
승인	강 문 현		260-1	of page	1	개정일자	