



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V ⁼	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
630	0.047	SA033	±5 %	7.0 x 13.5 x 18.0	15.0±0.4	3.5±0.3

Same as PCMP 384 12473

- <But>
 - AEC-Q200 qualified
 - 1770 PBT gray case
 - LT 3.5±0.3mm

- Marking

47n J 630V PILKOR 384 MMKP

or

47n J 630V 384 MMKP PILKOR

Marking on the side or top

Marking on the side or top

- Packing Method (Vinyl)

Packing method	Vinyl	SPQ	PQ
8242 450 40122	200 (8242 456 40006)	1000 (8242 451 30191)	4000 (8242 451 30281)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	18-01-25
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (두원전자)	PCMP 384 SA033		개정 No		
승인	강문현		190-1	of page	1	개정일자	

For part lists see PCMP 384 12473

Include :

Delete :

- Cell code : 4342 472 S0224 for PCMP 384 SA033

For manufacturing instruction see PCMP 384 12473 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

2) 1770 PBT gray case – 4342 433 20091

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	12	-4.5%/+ 4.5%	500	5	1050V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-01-25
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (두원전자)	PCMP 384 SA033		개정 No	
승인	강문현		260-1	of page	1	개정일자