



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V ⁼	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
2000	0.010	SA036	±5 %	10.0 × 16.5 × 18.0	15.0±0.4	5.0±1.0

Same as PCMP 384 92103

<But>

- 1710 PBT gray case
- Dissipation factor (Tangent of loss angle, x 10⁻⁴) : ≤ 5 at 1kHz, ≤ 15 at 100kHz
- Marking

10n J 2000V PILKOR 384 MMKP

Marking on the side or top

or

10n J 2000V 384 MMKP PILKOR
--

Marking on the side or top

- Packing Method (Loose in box)

Packing method	SPQ	PQ
8242 450 40026	1000 (8242 451 30211)	4000 (8242 451 30301)

부서	제품개발1팀	Type Specification			최초작성일	18-05-25
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (현대모비스)	PCMP 384 SA036		개정 No	
승인	강 문 현		190-1	of page	1	개정일자

For part lists see PCMP 384 92103

Include :

Delete :

- Cell code : 4342 472 S0213 for PCMP 384 SA025 & SA036

For manufacturing instruction see PCMP 384 92103 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

2) 1710 PBT gray case – 4342 433 20121

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	8	-4.5%/+ 4.5%	500	5	3200V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-05-25
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (현대모비스)	PCMP 384 SA036		개정 No	
승인	강문현		260-1	of page	1	개정일자