



$d_t = 0.8 + 0.08/-0.05 \text{ mm}$

Voltage V ⁼	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
2000	0.0075	SA039	±5 %	7.5 x 18.5 x 18.0	15.0±0.4	3.7±0.3

Same as PCMP 384 92752

<But>

- AEC-Q200 qualified
- 1775H PBT gray case
- LT 3.7±0.3mm

- Marking

7n5 J 2000V PILKOR
384 MMKP

or

7n5 J 2000V
384 MMKP
PILKOR

Marking on the side or top

Marking on the side or top

- Packing Method (Tray)

Packing method	SPQ (Tray)	SPQ (Bundle)	PQ (Outer box)
8242 450 40258	220 (8242 451 31031)	1540	3080 (8242 451 30671)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-10-10
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA039		개정 No	
승인	강문현				190-1	of page

For part lists see PCMP 384 92752

Include :

Delete :

- Cell code : 4342 472 S0236

For manufacturing instruction see PCMP 384 92752 However :

<But>

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 1775H PBT gray case – 4342 433 20641

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	8	-4.5%/+ 4.5%	500	5	3200V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-10-10
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA039		개정 No	
승인	강문현		260-1	of page	1	개정일자