



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V <sup>=</sup>	Cap. μF	Code PCMP 384 .....	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
2000	0.0091	SA043	±5 %	7.5 x 18.5 x 18.0	15.0±0.4	3.7±0.3

Same as PCMP 384 92912

<But>

- AEC-Q200 qualified
- 1775H PBT gray case
- LT 3.7±0.3mm

- Marking

9n1 J 2000V PILKOR  
384 MMKP ....

or

9n1 J 2000V  
384 MMKP ....  
PILKOR

Marking on the side or top

Marking on the side or top

- Packing Method (Tray)

Packing method	SPQ ( Tray )	SPQ ( Bundle )	PQ ( Outer box )
8242 450 40258	220 ( 8242 451 31031 )	1540	3080 ( 8242 451 30671 )

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-11-30
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA043		개정 No	
승인	강문현				190-1	of page

---

For part lists see PCMP 384 92912

---

Include :

Delete :

- Cell code : 4342 472 S0241

---

For manufacturing instruction see PCMP 384 92912 However :

---

<But>

- LOA

1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D )

2) 1775H PBT gray case – 4342 433 20641

- R/D Testing

Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	8	-4.5%/+ 4.5%	500	5	3200V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-11-30
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA043		개정 No	
승인	강문현		260-1	of page	1	개정일자