



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V <sup>r</sup>	Cap. μF	Code PCMP 384 .....	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
800	0.047	SA051	±5 %	8.5 x 15.0 x 18.0	15.0±0.4	5.0±1.0

Same as PCMP 384 M2473

<But>

- Automotive (AEC-Q200 Qualified)
- 1785PBT Gray case
- Marking

47n J 800V PILKOR 384 MMKP ....
------------------------------------

47n J 800V 384 MMKP .... PILKOR
---------------------------------------

Marking on the side or top or Marking on the side or top

- Packing Method (Vinyl)

Packing method	Vinyl	SPQ	PQ
8242 450 40123	200 (8242 456 40006)	1000 (8242 451 30201)	4000 (8242 451 30291)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	19-10-10
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (대우전자부품)	PCMP 384 SA051		개정 No	
승인	강 문 현		190-1	of page 1	개정일자	

For part lists see PCMP 384 M2473

Include :

Delete :

- Cell code : 4342 472 S0248 for PCMP 384 SA051

For manufacturing instruction see PCMP 384 M2473

<But>

- LOA

1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D )

2) 1785 PBT gray case – 4342 433 20101

- R/D Testing

Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
7	12	-4.5%/+ 4.5%	500	5	1350V

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-10-10
작성	백영섭	MMKP		PCMP 384 SA051		개정 No	
		RADIAL POTTED CAPACITORS					
승인	강문현	(대우전자부품)		260-1	of page	1	개정일자