



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V <sup>=</sup>	Cap. μF	Code PCMP 384 .....	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
2000	0.0033	SA006	±5.0 %	6.0 x 12.0 x 18.0	15.0±0.4	5.0±1.0
1600	0.0068	SA007	±5.0 %	6.0 x 12.0 x 18.0	15.0±0.4	5.0±1.0

Same as PCMP 384 92332 / 82682

<But>

- Automotive (AEC-Q200 Qualified)

- Packing Method (LOOSE IN BOX)

12 NC	Packing method	SPQ	PQ
PCMP 384 SA006 PCMP 384 SA007	8242 450 40023	1000 (8242 451 30181)	4000 (8242 451 30271)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	15-04-15
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (대명)	PCMP 384 SA006 PCMP 384 SA007		개정 No	1	
승인	강 문 현		190-1	of page	1	개정일자	16-11-23

---

For part lists see PCMP 384 92332 / 82682

---

Include :

Delete :

- Cell code :

. 4342 472 S0187 ( PCMP 384 SA006 )

. 4342 472 S0188 ( PCMP 384 SA007 )

---

For manufacturing instruction see PCMP 384 92332 / 82682 However :

---

**<But>**

- LOA

1) Pull off force  $\geq$  1000g

2) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

박 주 영		MMKP RADIAL POTTED CAPACITORS ( 대명 )	PCMP 384 SA006 PCMP 384 SA007		15-04-15			
백 영 섭					QS	A4		
QS	강문현		15-04-15	1	260-1	010	QS	A4
(C) PILKOR ELECTRONICS CO., LTD. 2015								