


$$d_t = 0.6 + 0.06/-0.05 \text{ mm}$$

Voltage V [⊖]	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
1000	0.0062	SA013	±5 %	6.0 × 12.0 × 12.5	10.0±0.4	3.4±0.3
630	0.022	SA014	±5 %	5.0 × 11.0 × 12.5	10.0±0.4	3.4±0.3

Same as PCMP 384 D2622 / C2223
<But>

- Automotive (AEC-Q200 Qualified)
- PBT gray case
- LT=3.4±0.3mm
- Marking



Marking on the side

- Packing Method (Loose in Box - Vinyl)

Product code	Packing method	Vinyl	SPQ	PQ
PCMP 384 SA013	8242 450 40107	250 (8242 456 40001)	1000 (8242 451 30181)	4000 (8242 451 30271)
PCMP 384 SA014	8242 450 40122	250 (8242 456 40006)	1500 (8242 451 30191)	6000 (8242 451 30281)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-01-13
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (LGIT)	PCMP 384 SA013 PCMP 384 SA014		개정 No	1	
승인	강 문 현		190-1	of page	1	개정일자	16-11-23

For part lists see PCMP 384 D2622 / C2223

Include :

Delete :

- Cell code : 4342 472 S0195 for PCMP 384 SA013
4342 472 S0196 for PCMP 384 SA014
-

For manufacturing instruction see PCMP 384 D2622 / C2223 However :

<But>

- LOA

- 1) Welding depth ; 0.5 ± 0.1 mm
- 2) Pull off force ≥ 1000 gf
- 3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 4) 1260 PBT gray case – 4342 433 20021
1250 PBT gray case – 4342 433 20011

박 주 영		MMKP RADIAL POTTED CAPACITORS (LGIT)			PCMP 384 SA013 PCMP 384 SA014		16-01-13	
백 영 섭								
			16-01-13	1	260-1	010	QS	A4
QS	강 문 현	PILKOR ELECTRONICS 2016						