



$$d_t = 0.6 + 0.06/-0.05 \text{ mm}$$

Voltage V <sup>⊖</sup>	Cap. μF	Code PCMP 384 .....	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
630	0.010	SA017	±5 %	5.0 x 11.0 x 12.5	10.0±0.4	3.7±0.3

Same as PCMP 384 12103

<But>

- Automotive (AEC-Q200 Qualified)
- 1250 PBT gray case
- Marking

10n J 630V 384 MMKP .... PILKOR
---------------------------------------

Marking on the side

- Packing Method (Vinyl)

Product code	Packing method	Vinyl	SPQ	PQ
PCMP 384 SA017	8242 450 40122	250 (8242 456 40006)	1500 (8242 451 30191)	6000 (8242 451 30281)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-06-09
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA017		개정 No	3	
승인	강 문 현		190-1	of page	1	개정일자	17-03-21

---

For part lists see PCMP 384 12103

---

Include : Delete :  
- Cell code : 4342 472 S0202 for PCMP 384 SA017

---

For manufacturing instruction see PCMP 384 12103 However :

---

<But>

- LOA

- 1) Welding depth ;  $0.5 \pm 0.1$ mm
- 2) Pull off force  $\geq 1000$ gf
- 3) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )
- 4) 1250 PBT gray case – 4342 433 20011

박 현 속		MMKP RADIAL POTTED CAPACITORS (LG전자)			PCMP 384 SA017		16-06-09	
백 영 섭							QS	A4
		16-06-09	1	260-1	010	QS	A4	
QS	강 문 현	PILKOR ELECTRONICS 2016						