



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V ^r	Cap. μF	Code PCMP 384	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
2000	0.037	SA023	±5 %	13.0 x 23.0 x 26.0	22.5±0.4	3.5±0.3

Same as PCMP 384 92243

<But>

- AEC-Q200 Qualified
- 2513 PBT gray case
- Capacitance 37nF & LT 3.5±0.3mm
- Marking

37n J 2000V PILKOR 384 MMKP

Marking on the side or top

- Packing Method (Tray)

Packing method	Sponge	SPQ	PQ
8242 450 40238	8242 456 20009	110 (8242 451 31021)	660 (8242 451 30701)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-11-17
작성	김 세 지	MMKP RADIAL POTTED CAPACITORS (현대자동차)	PCMP 384 SA023		개정 No	1	
승인	강 문 현				190-1	of page	1

For part lists see PCMP 384 92243

Include :

Delete :

- Cell code : 4342 472 S0212 for PCMP 384 SA023

For manufacturing instruction see PCMP 384 92243 However :

<But>

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 2513 PBT gray case – 4342 433 20181

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	10	-4.5%/+ 4.5%	500	5	3200V

부서	제품개발1팀	Type Specification			최초작성일	16-11-17
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (현대자동차)	PCMP 384 SA023		개정 No	
승인	강문현		260-1	of page	1	개정일자