

$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$


Voltage V ^r	Cap. μF	Code PCMP 384	C-tol.	Dimensions b × h × l mm	P mm	Lt mm
2000	0.01	SA034	±5 %	8.5 x 15.0 x 18.0	15.0±0.4	3.4±0.3

Same as PCMP 384F92103

<But>


- AEC-Q200 qualified
- 1785 PBT gray case
- LT 3.4±0.3mm

- Marking



Marking on the side or top

or



Marking on the side or top

- Packing Method (Vinyl)

Packing method	Vinyl	SPQ (Inner box)	PQ (Outer box)
8242 450 40123	200ea	1000ea (8242 451 30201)	4000ea (8242 451 30291)

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-01-29
작성	백영섭	MMKP RADIAL POTTED CAPACITORS (만도)	PCMP 384 SA034		개정 No	1
승인	강문현				190-1	of page

For part lists see PCMP 384F92103

Include :

Delete :

- Cell code : 4342 472 S0225 for PCMP 384 SA034

For manufacturing instruction see PCMP 384F92103 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

2) 1785 PBT gray case – 4342 433 20101

- R/D Testing

Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	8	-4.5%/+ 4.5%	500	5	3300V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-01-29
작성	백영섭	MMKP	PCMP 384 SA034		개정 No	
		RADIAL POTTED CAPACITORS				
승인	강문현	(만도)	260-1	of page	1	개정일자