


$$d_t = 0.6 + 0.06/-0.05 \text{ mm}$$

Voltage V ⁼	Cap. μF	Code	C-tol.	Dimensions	P mm
		PCMP 384		b x h x l mm	
630	0.0068	SA046	±5 %	5.0 x 11.0 x 12.5	10.0±0.4
1000	0.0033	SA047	±5 %	5.0 x 11.0 x 12.5	10.0±0.4

Same as PCMP 384 15682, D5332

<But>

- AEC-Q200 qualified
- 1250 PBT gray case
- Marking



Marking on the side

- Packing Method (Ammo packing)

Packing method	SPQ	PQ
	(Inner box)	(Outer box)
8242 450 40051	700 (8242 451 10111)	3500 (8242 451 30521)

- Test Requirements

See PCMP 384 SA...(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	19-02-22
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (Vestel)	PCMP 384 SA046		개정 No	
			PCMP 384 SA047			
승인	강 문 현		190-1	of page	1	개정일자

For part lists see PCMP 384 15682, D5332

Include :

Delete :

- Cell code :

4342 472 S0244 for PCMP 384 SA046

4342 472 S0245 for PCMP 384 SA047

For manufacturing instruction see PCMP 384 15682, D5332 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

2) 1250 PBT gray case -4342 433 20011

- R/D Testing

Code PCMP 384	Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test V oltage
	1kHz	100kHz		V	nA	
SA046	5	8	-4.5%/+ 4.5%	500	5	1050V
SA047	5	8	-4.5%/+ 4.5%	500	5	1650V

부서	제품개발1팀	Manufacturing Specification				최초작성일	18-02-22
작성	백 영 섭	MMKP	PCMP 384 SA046		개정 No		
		RADIAL POTTED CAPACITORS	PCMP 384 SA047				
승인	강 문 현	(Vestel)	260-1	of page	1	개정일자	