



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage V <sup>=</sup>	Cap. μF	Code PCMP 384 .....	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
2000	0.02	SA048	±5 %	10.0 x 19.5 x 26.0	22.5±0.4	3.7±0.3

Same as PCMP 384 22103

<But>

- AEC-Q200 qualified
- Value extensions 20nF & 2510PBT\_Gray case
- LT 3.7±0.3mm

- Marking

20n J 2000V PILKOR 384 MMKP ....
-------------------------------------

Marking on the side or top

20n J 2000V 384 MMKP .... PILKOR
--

Marking on the side or top

- Packing Method (Tray)

Packing method	SPQ ( Tray )	SPQ ( Bundle )	PQ ( Outer box )
8242 450 40259	150ea ( 8242 451 31021 )	1050ea	1050ea ( 8242 451 30701 )

- Test Requirements

See PCMP 384 SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	19-07-18
작성	백 영 섭	MMKP RADIAL POTTED CAPACITORS (LG전자)	PCMP 384 SA048		개정 No	
승인	강 문 현		190-1	of page	1	개정일자

For part lists see PCMP 384 22103

Include :

Delete :

- Cell code : 4342 472 S0246

For manufacturing instruction see PCMP 384 22103

<But>

- LOA

- 1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )
- 2) 2510 PBT gray case – 4342 433 20161

- R/D Testing

Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
1kHz	100kHz		V	nA	
5	8	-4.5%/+ 4.5%	500	5	3200V

부서	제품개발1팀	Manufacturing Specification			최초작성일	19-07-18
작성	백영섭	MMKP	PCMP 384 SA048		개정 No	
		RADIAL POTTED CAPACITORS				
승인	강문현	(LG전자)	260-1	of page	1	개정일자