



$$d_t = 0.6 + 0.06 / -0.05 \text{ mm}$$

Voltage V ⁼	Cap. μF	Code PCMT 468	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
250V	0.22	SA001	$\pm 5\%$	5.0 x 11.0 x 12.5	5.0 \pm 0.4	5.0 \pm 1.0

Same as PCMT 468D42224

<BUT>

- Automotive (AEC-Q200 Qualified)
- PBT_Gray case
- Marking

220n J 250V 468 MKT PILKOR

Marking on the side

- Packing Method (Loose in box)

Packing method	SPQ (Inner box)	PQ (Outer box)
8242 450 40023	1500 (8242 451 30181)	6000 (8242 451 30271)

- Test Requirements

See PCMT 468 SAxxx (sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-11-08
작성	백 영 섭	MKT RADIAL POTTED CAPACITORS (성일전자)	PCMT 468 SA001		개정 No	
승인	강 문 현		190-1	of page	1	개정일자
(C) PILKOR ELECTRONICS						

For part lists see PCMT 468D42224

Include : Delete :

- Cell code for PCMT 468 SA001 : 4342 471 21054

For manufacturing instruction see PCMT 468D42224 However :

<BUT>

-. LOA

- 1) Liquid epoxy : 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

- 2) 1250 PBT Gray case : 4342 433 20011

부서	제품개발1팀	Type Specification			최초작성일	18-11-08
작성	백 영 섭	MKT RADIAL POTTED CAPACITORS (성일전자)	PCMT 468 SA001		개정 No	
승인	강 문 현		260-1	of page	1	개정일자

(C) PILKOR ELECTRONICS