

$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$


Voltage Vdc	Cap. μF	Code PCPW 223	C-tol. %	Dimensions b × h × l mm	P mm	lt mm
100	9.4	SA0006	±10	11.0 x 18.5 x 18.0	15.0±0.4	3.4±0.3

Same as PCPW 223F21945

<But>

- Automotive (AEC-Q200 Qualified)
- 1711 PBT gray case
- LT=3.4±0.3mm

- Marking



Marking on the side

- PACKING METHOD (Tray arrange)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40236	8242 456 20011	150 (8242 451 31031)	1800 (8242 451 30671)

-Test Requirements

See PCPW 223SA....(sh. 190-1)

부서	제품개발팀	Type Specification				최초작성일	15-12-11
작성	김 세 지	MKT RADIAL POTTED CAPACITORS (LGIT)	PCPW 223SA0006			개정 No	3
승인	강 문 현					190-1	of page

For part lists see PCPW 223F21945

Include :

Delete :

- Cell code : 4342 492 22070

For manufacturing instruction see PCPW 223F21945 However :

<But>

- LOA

- 1) Welding depth ; 0.5 ± 0.1 mm
- 2) Pull off force ≥ 1000 gf
- 3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 4) 1711 PBT gray case – 4342 433 20131

박 주 영		MKT RADIAL POTTED CAPACITORS (LGIT)			PCPW 223SA0006		15-12-11	
백 영 섭							QS	A4
			15-12-11	1	260-1	010	QS	A4
QS	강 문 현		PILKOR ELECTRONICS 2015					

