



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code PCPW 223	C-tol. %	Dimensions b x h x l mm	P mm	It mm
35	4.7	SA0015	± 10	8.5 x 15.0 x 18.0	15.0 \pm 0.4	5.0 \pm 1.0

Same as PCPW 223FV1475

<But>

- Automotive (AEC-Q200 qualified)
- 1785 PBT gray case

- PACKING METHOD (Tray arrange)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40236	8242 456 20011	200 (8242 451 31031)	2400 (8242 451 30671)

-Test Requirements

See PCPW 223SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	16-05-23
작성	김 세 지	MKT RADIAL POTTED CAPACITORS (Blast)	PCPW 223SA0015		개정 No	1
승인	강 문 현		190-1	of page	1	개정일자

For part lists see PCPW 223F21475

Include :

Delete :

- Cell code : 4342 492 12010

For manufacturing instruction see PCPW 223F21475 However :

<But>

- LOA

1) Welding depth ; 0.5 ± 0.1 mm

2) Pull off force ≥ 1000 gf

3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

4) 1785 PBT gray case – 4342 433 20101

박 현 속		MKT RADIAL POTTED CAPACITORS (Blast)			PCPW 223SA0015		16-05-23	
백 영 섭							QS	A4
			15-12-23	1	260-1	010		
QS	강 문 현		PILKOR ELECTRONICS 2016					