



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code PCPW 223	C-tol. %	Dimensions b x h x l mm	P mm	It mm
50	19	SA0017	± 10	12.0 x 22.0 x 26.0	22.5 \pm 0.4	5.0 \pm 1.0

Same as PCPW 223J21196

<But>

- Automotive(AEC-Q200 qualified) & PBT (gray) case
- Rated voltage 50Vdc
- Marking

19u K 50V PILKOR
223 MKT WK....

Marking on the top or side

- PACKING (Tray arrange)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40238	8242 456 20009	120 (8242 451 31021)	720 (8242 451 30701)

-Test Requirements

See PCPW 223SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-06-13
작성	김 세 지	MKT RADIAL POTTED CAPACITORS (이지트로닉스)	PCPW 223SA0017		개정 No	1	
승인	강 문 현		190-1	of page	1	개정일자	16-11-23

For part lists see PCPW 223J21226

Include :

Delete :

- Cell code for PCPW 223SA0017 : 4342 492 23010

For manufacturing instruction see PCPW 223J21196

<But>

- LOA

- 1) Welding depth ; 0.5 ± 0.1 mm
- 2) Pull off force ≥ 1000 g
- 3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 4) PBT case (Gray) ; 4342 433 20051

박 현 속		MKT RADIAL POTTED CAPACITORS (이지트로닉스)			PCPW 223SA0017		16-06-13	
백 영 섭							QS	A4
			16-06-13	1	260-1	010	QS	A4
QS	강 문 현		PILKOR ELECTRONICS 2016					