



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code PCPW 223	C-tol. %	Dimensions b × h × l mm	P mm	It mm
35	15	SA0026	±10	11.5 x 21.0 x 26.0	22.5±0.4	5.0±1.0

Same as PCPW 223JV1196

<But>

- Automotive(AEC-Q200 Qualified)
- 2512 PBT case (Gray) & Capacitance 15uF K
- Marking

15u K 35V PILKOR
223 MKT WK....

Marking on the top or side

- PACKING METHOD (Tray packing)

Packing method	Sponge	SPQ (Tray)	PQ (Outer box)
8242 450 40251	8242 456 20009	130 (8242 451 31021)	1560 (8242 451 31061)

-Test Requirements

See PCPW 223SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	19-05-27
작성	백 영 섭	MKT RADIAL POTTED CAPACITORS (유라코퍼레이션)	PCPW 223SA0026			개정 No	
승인	강 문 현		190-1	of page	1	개정일자	

For part lists see PCPW 223JV1196

Include :

Delete :

- Cell code :
. 4342 492 S0037

For manufacturing instruction see PCPW 223JV1196 However :

<But>

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

2) PBT case (Gray)

- 2512 ; 4342 433 20041

- R/D

Cap. [uF]	Tan d (x 10 ⁻⁴)			Cap test limit	R. insul		Healing & Test Volt age
	1kHz	10kHz	100kHz		V	nA	
15.0	60	130	600	-9.5%/+ 9.5%	100	75	60

부서	제품개발1팀	Manufacturing Specification				최초작성일	19-05-27
작성	백 영 섭	MKT RADIAL POTTED CAPACITORS (유라코퍼레이션)		PCPW 223SA0026		개정 No	
승인	강 문 현					260-1	of page