



$$dt = 1.2 + 0.12 / -0.05 \text{ mm}$$

Voltage V <sup>=</sup>	Cap. μF	Code		Dimensions		P mm	P1 mm	Lt mm
		PCPW 245	C-tol.	b × h × l	mm			
700V	12	SA0001	±10 %	20.0 × 35.0 × 42.0	37.5±0.7	10.2±0.5	5.0±1.0	

SAME AS PCPW 245QRA126

< BUT >

- Automotive (AEC-Q200 qualified)

- Packing Method :Arrange Packing

Packing method	Styrofoam	SPQ (Folding Plate )	PQ ( Outer box )
8242 450 40166	8242 456 30211	90 (8242 451 10221)	360 (8242 451 30851)

-Test Requirements

See PCPW 245SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	15-04-01
작성	김 세 지	MKP RADIAL POTTED CAPACITORS (LS산전)	PCPW 245SA0001		개정 No	1
승인	강 문 현		190-1	of page	1	개정일자

(C) PILKOR ELECTRONICS

-----For part lists see PCPW 245QRA126

Include :

Delete :

- Cell code : . 4342 494 22020(for PCPW 245QRA126)

-----  
For manufacturing instruction see PCPW 245QRA126 However :  
-----

- LOA

1) Welding depth ;  $0.6 \pm 0.1$ mm

2) Pull off force  $\geq 1000$ g

3) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

박 현 속		MKP					15-04-01	
엄 태 호		RADIAL POTTED CAPACITORS			PCPW 245SA0001		16-05-12	
		(LS산전)						
			15-04-01	1	260-1	010	QS	A4
QS	강문현	(C) PILKOR ELECTRONICS, LTD. 2016						