



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code PCPW 223 .....	C-tol. %	Dimensions b × h × l mm	P mm	It mm
100	10	SA0022	±10	11.5 x 21.0 x 26.0	22.5±0.4	5.0±1.0

Same as PCPW 223JV1196

<But>

- Automotive(AEC-Q200 qualified) & PBT (gray) case
- Capacitance ; 10uF
- Marking

10u K 100V PILKOR  
223 MKT WK....

Marking on the top or side

- PACKING METHOD( Tray packing )

Packing method	Sponge	SPQ ( Tray )	PQ ( Outer box )
8242 450 40238	8242 456 20009	130 ( 8242 451 31021 )	780 ( 8242 451 30701 )

-Test Requirements

See PCPW 223SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	16-10-10
작성	김 세 지	MKT RADIAL POTTED CAPACITORS (대명전자)	PCPW 223SA0022		개정 No	1	
승인	강 문 현				190-1	of page	1

For part lists see PCPW 223.....

Include :

Delete :

- Cell code :

. 4342 492 S0034(for PCPW 223SA0022)

For manufacturing instruction see PCPW 223..... However :

<But>

- LOA

1) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
1342 431 10225 - Hardener : MH-770D )

2) 2512PBT gray case : 4342 433 20041

- R/D

Cap. [uF]	Tan d ( x 10 <sup>-4</sup> )			Cap test limit	R. insul		Healing & Test Volt age
	1kHz	10kHz	100kHz		V	nA	
10	60	130	450	-9.5%/+ 9.5%	100	200	160

박 현 숙		MKT				PCPW 223SA0022		16-10-10		
백 영 섭		RADIAL POTTED CAPACITORS ( 대명전자 )								
			16-10-10	1	260-1	010	QS	A4		
QS	강 문 현		PILKOR ELECTRONICS 2016							