



$$d_t = 0.8 + 0.08/-0.05 \text{ mm}$$

Voltage Vdc	Cap. μF	Code PCPW 225	C-tol. %	Dimensions b x h x l	P mm	lt mm
630	3.3	SA0005	±10	18.0 x 28.0 x 31.0	27.5±0.4	3.4±0.3

Same as PCPW 225LQ2335

<But>

- Automotive(AEC-Q200 qualified)
- LT=3.4±0.3 & wire 0.8Φ
- Dissipation factor (Tan δ, x 10⁻⁴) ; ≤ 10 at 1kHz

- PACKING METHOD (Arrange Packing)

Packing method	Sponge	SPQ (Inner box)	PQ (Outer box)
8242 450 40102	8242 456 30201	100 (8242 451 10211)	500 (8242 451 30751)

-Test Requirements

See PCPW 225SA....(sh. 190-1)

부서	제품개발1팀	Type Specification				최초작성일	15-04-20
작성	김 세 지	MKP RADIAL POTTED CAPACITORS (만도)	PCPW 225SA0005			개정 No	2
승인	강 문 현					190-1	of page

For part lists see PCPW 225LQ2335

Include :

Delete :

- Cell code :

. 4342 482 S0072 (PCPW 225SA0005)

For manufacturing instruction see PCPW 225LQ2335 However :

<But>

- LOA

1) Welding depth ; 0.5 ± 0.1 mm

2) Pull off force ≥ 1000 g

3) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D

1342 431 10225 - Hardener : MH-770D)

박 주 영		MKP RADIAL POTTED CAPACITORS (만도)				PCPW 225SA0005		15-04-20	
백 영 섭								QS	A4
			15-04-20	1	260-1	010			
QS	강 문 현		(C) PILKOR ELECTRONICS CO., LTD. 2015						