

dt = 0.8 + 0.08 / -0.05 mm

Voltage V~	Cap.	Code		Dimensions	D	Lt	
	υF	PCX2 339	C-tol.	C-tol. b \times h \times l			
	•	*****		mm	mm 		
305	2.2	SA0001	$\pm 20~\%$	15.0 x 25.0 x 31.0	27.5 ± 0.4	3.2 ± 0.3	

Same as PCX2 339LA....

< BUT >

- AEC-Q200 Qualification

 $- Lt = 3.2 \pm 0.3 \, mm$

- Packing Method (LOOSE IN BOX)

12 NC	Packing method	SPQ (Inner box)	PQ (Outer box)	
PCX2 339SA0001	8242 450 40026	250 (8242 451 30211)	1000 (8242 451 30301)	

K	
3	
4 10 1	
7	_
	(

							대출	일
박	주 영	MKP			PCX2 339SA0001		11-06-08	
김	희 철	RADIAL POTTED CAPACITORS						
		(KOSTAL)						
			11-06-08	1	190-1	010	QS	A4
QS	박범학	(C) PILKOR ELECTRONICS, LTD. 2011						

$ \bigcirc \langle$	

For part lists see PCX2 339LA	
Include:	Delete:

- Cell code:

. 4342 485 14033 (cell for PCX2 339L70225)

For manufacturing instruction see PCX2 339LA.... However:

< BUT >

- AEC-Q200 Qualification

 $-Lt = 3.2 \pm 0.3 \text{ mm}$

4342 800 00061

박 주 영 	MKF	11-06			6-08		
김 희 철	RADIAL POTTED CAPACITORS			PCX2 339SA0001			
	(KOSTAL)						
		11-06-08	1	260-1	010	QS	A4
QS 박범학	(C) PILKOR ELECTRONICS, LTD. 2011						

