



$$dt = 0.8+0.08/-0.05\text{mm}$$

Voltage V~	Cap. μF	Code	C-tol.	Dimensions	P mm	Lt mm
		PCY2 130		b x h x l mm		
300	0.01	S00022	$\pm 10\%$	5.0 x 11.0 x 18.0	15.0 ± 0.4	5.0 ± 1.0

Same as PCY2 130F31103

<BUT>

-Automotive grade

-Packing Method : (Vinyl Packing)

Packing method	vinyl	SPQ	PQ
		(Inner box)	(Outer box)
8242 450 40121	200	1000 (8242 451 30181)	4000 (8242 451 30271)

박 주 영		MKP					15-01-23	
김 세 지		RADIAL POTTED CAPACITORS			PCY2 130S00022			
		(Diamond)						
			15-01-23	1	190-1	010	QS	A4
QS	박범학	(C) PILKOR ELECTONICS, LTD. 2015						

For part lists see PCY2 130F31103

Include :

Delete :

- Cell code :

. 4342 479 S0024 (for PCY2 130S00019)

For manufacturing instruction see PCY2 130F31103 However :

<BUT>

- Automotive grade

- LOA

1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)

박 주 영		MKP						15-01-23	
김 세 지		RADIAL POTTED CAPACITORS			PCY2 130S00022				
		(Diamond)							
			15-01-23	1	260 - 1	010	QS	A4	
QS	박범학	(C) PILKOR ELECTONICS, LTD. 2015							