



$$dt = 0.6+0.06/-0.05\text{mm}$$

Voltage V~	Cap. $\mu\text{F}$	Code PCY2 130 .....	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
300	0.01	SA0013	$\pm 10\%$	6.0 x 12.0 x 12.5	10.0 $\pm$ 0.4	3.4 $\pm$ 0.3

Same as PCY2 130D31103

<BUT>

- Automotive (AEC-Q200 Qualified)
- PBT(gray) case
- LT 3.4 $\pm$ 0.3mm

- Packing Method : Vinyl packing

Packing method	Vinyl	SPQ	PQ
8242 450 40107	250 (8242 456 40001)	1000 (8242 451 30181)	4000 (8242 451 30271)

-Test Requirements

See PCY2 130SA...(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	16-09-23
작성	김 세 지	MKP RADIAL POTTED CAPACITORS (만도)	PCY2 130SA0013		개정 No	1
승인	강 문 현		190-1	of page	1	개정일자

(C) PILKOR ELECTRONICS

-----  
 For part lists see PCY2 130D31103  
 -----

Include :

Delete :

- Cell code :

. 4342 479 S0038 (for PCY2 130SA0013)

-----  
 For manufacturing instruction see PCY2 130D31103 However :  
 -----

**<BUT>**

- LOA

- 1) Pull off force  $\geq$  1000g
- 2) Liquid epoxy ; 770D ( 1342 431 10224 - Resin : SE-770 UMB D  
 1342 431 10225 - Hardener : MH-770D )
- 3) 1260 PBT (Gray) case : 4342 433 20021

- R/D

Cap. [uF]	Tan d ( x 10 <sup>-4</sup> )		Cap test limit	R. insul		Healing & Test Voltage
	1kHz	100kHz		V	nA	
0.01	7	18	-9.5%/+ 9.5%	100	6	2500V

박 현 속		MKP				16-09-23	
백 영 섭		RADIAL POTTED CAPACITORS				PCY2 130SA0013	
		(마드)					
			16-09-23	1	260 - 1	010	QS A4
QS	강문현	PILKOR ELECTONICS 2016					