



$dt = 0.8+0.08/-0.05\text{mm}$

Voltage V~	Cap. μF	Code PCY2 130	C-tol.	Dimensions b x h x l mm	P mm	Lt mm
300	0.15	SA0019	$\pm 10\%$	11.0 x 21.0 x 31.0	27.5 ± 0.4	3.7 ± 0.3

Same as PCY2 130L31224

<BUT>

- Automotive(AEC-Q200 Qualified)
- 3011 PBT gray case, $0.15\mu\text{F} \pm 10\%$ & $Lt=3.7 \pm 0.3\text{mm}$
- Withstanding(DC) Voltage(Cut-off current 10mA) ; 3400V for 1min.

- Packing Method : Arrange

Packing method	Sponge	SPQ (Folding plate)	PQ (Outer box)
8242 450 40181	8242 456 30061	100 (8204 116 60111)	1000 (8242 451 30871)

-Test Requirements

See PCY2 130SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-03-20
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (영화테크)	PCY2 130SA0019		개정 No	
승인	강 문 현		190-1	of page	1	개정일자
(C) PILKOR ELECTRONICS						

For part lists see PCY2 130L31224

Include :

Delete :

- Cell code :

. 4342 479 S0047

For manufacturing instruction see PCY2 130L31224 However :

<BUT>

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 3011 PBT gray case – 4342 433 20211

- R/D

Cap. [uF]	Tan d (x 10 ⁻⁴)		Cap test limit	R. insul		Healing & Test Voltage
	1kHz	100kHz		V	nA	
0.15	7	70	-9.5%/+ 9.5%	100	6	2500V

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-03-20
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (영화테크)	PCY2 130SA0019		개정 No	
승인	강 문 현				260-1	of page

(C) PILKOR ELECTRONICS