



$$dt = 0.8 + 0.08 / -0.05 \text{ mm}$$

Voltage V~	Cap. μF	Code PCY2 130	C-tol.	Dimensions $b \times h \times l$ mm	P mm	A mm	B mm
300	0.1	SA0023	$\pm 10 \%$	10.0 x 19.5 x 26.0	22.5 ± 0.6	2.5 ± 0.5	2.5 ± 0.5

Same as PCY2 130J31104

<BUT>

- Automotive(AEC-Q200 Qualified)
- 2510 PBT gray case & \sqcap -forming A,B : $2.5 \pm 0.5 \text{ mm}$
- Rated DC voltage : 1000Vdc
- Withstanding(DC) Voltage(Cut-off current 10mA) ; 3400V for 1min.
- Packing Method : Arrange

Packing method	Paper bar	Sponge	SPQ (Folding plate)	PQ (Outer box)
8242 450 40275	8242 455 10091	8242 456 30041	200ea (8204 116 50912)	1000ea (8242 451 31151)

-Test Requirements

See PCY2 130SA....(sh. 190-1)

부서	제품개발1팀	Type Specification			최초작성일	18-07-16
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (LG전자)	PCY2 130SA0023		개정 No	2
승인	강 문 현		190-1	of page	1	개정일자

(C) PILKOR ELECTRONICS

For part lists see PCY2 130J31104

Include :

Delete :

- Cell code :

. 4342 479 S0027

For manufacturing instruction see PCY2 130J31104 However :

<BUT>

- LOA

- 1) Liquid epoxy ; 770D (1342 431 10224 - Resin : SE-770 UMB D
1342 431 10225 - Hardener : MH-770D)
- 2) 2510 PBT gray case – 4342 433 20161

부서	제품개발1팀	Manufacturing Specification			최초작성일	18-07-16
작성	백 영 섭	MKP RADIAL POTTED CAPACITORS (LG전자)	PCY2 130SA0023		개정 No	
승인	강 문 현				260-1	of page

(C) PILKOR ELECTRONICS